





HEATIT ACTUATOR 24VDC

Actuator for waterbased heating systems

Art.no 4590031

GTIN 7071236018971

Compact electrothermal actuator for controlling waterbased heating systems. Can be regulated manually or on a signal from a thermostat or external regulator.

PRODUCT FEATURES

Electrothermal actuator (telestat) for energy-efficient control of waterbased heating and cooling systems.

Energy-efficient thanks to a low power consumption.

Simple installation without tool.

Compact design, low dimensions.

Open/Close indicator.

NC - Normally closed.

Silent.

High functional reliability and long life.

Valve test.

Manual opening function.

360° installation position.

Always. Fits. Perfectly.

Durable and reliable high-quality materials.

Made in EU.

Tested quality confirmed by the TÜV Rheinland according to the IEC 60730-2-14.

ELECTRO TECHNICAL DATA	
Voltage	24VDC
Own power usage (Volt)	1W
Protection grade (IP)	IP54
Declarations	CE declaration
Operating power	85mA
Max start current	470mA









MAINTENANCE

Cable must not be removed. The actuator must not be disassembled or opened! Otherwise maintenance-free.

PRODUCT INFO RETURN AND RECYCLING

The product must be recycled as electronic waste.

INSTALLATION AND STORAGE DATA

Max installation temperature 60°C Ambient Storage Temperature -25 til 60°C

Range

PRODUCT DIMENSIONS

Product width	38mm	Product height	75mm
Product length	45mm	Product weight	113g

LOGISTICAL DATA (F-PACK)

Width	54mm	Height/diameter	90mm	
Length	75mm	Weight	130g	
GTIN	7071236018971	Unit	ВОХ	
Consists of unit	EA	Quantity	1	

LOGISTICAL DATA (M-PACK)

Width	320mm	Height/diameter	280mm	
Length	470mm	Weight	13550g	
GTIN	17071236018978	Unit	CARTON	
Consists of unit	вох	Quantity	100	

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com and/or documents.heatit.com
Heatit Controls AB can not be held liable for any type of errors or omittances in our product information.
Product specifications may change without further notice.







Heatit Actuator 24V can be ordered from www.heatit.com/4590031

All additional documentation are available on the above adress and on documents.heatit.com/4590031





